

►► Built for a Lifetime

► Mach III GT Series



The Mach III GT Series of CNC routers from Komo Machine has been developed specifically for the customer who requires a premier machine with more flexibility, more customizable options and more table than a Mach III. These machines feature a moving gantry with table sizes available up to 120" (3048mm) in the Y axis and 110' (33,000mm) in the X axis, and can be configured with multiple spindles, moulder heads, horizontal spindles etc.

Features

- ◆ Four-pole, 18HP (13.2kw), 24,000 RPM, HSK 63F, fan-cooled spindle (standard; other spindle options available)
- ◆ 15 position automatic tool changer with aggregate capability (optional additional 15 position tool changer available)
- ◆ Air blast for optimal dust/chip evacuation and cooling of the cutting tool
- ◆ Advanced Fanuc HVI servo system tuned for optimum acceleration and deceleration
- ◆ Tool touch-off device with automatic tool data uploading
- ◆ Fanuc Panel i control with integrated PC
- ◆ Precision machined aluminum table (2") with options available
- ◆ Pressurized automatic centralized lubrication system
- ◆ KOMO Production Manager and Machine Monitoring software
- ◆ 19" touch screen display

Construction

- ◆ FEA "Finite Element Analysis" engineered structure
- ◆ Heavy-duty steel fabrication
- ◆ Closed-loop counterbalance system minimizes plant air consumption

KOMO

One Komo Drive
Lakewood, NJ 08701
www.komo.com

Toll Free: 800-255-5670
Phone: 732-719-6222
Fax: 732-579-5443

Mach III GT Series - Technical Data

Spindle

Quantity	One (1) standard, additional depending on gantry width
Type	18HP (13.2kw), four-pole, fan cooled (standard)
RPM	Up to 24,000, fully programmable
Taper	HSK 63F

Table

525	60" x 300" (1524mm x 7620mm)
625	72" x 300" (1829mm x 7620mm)
825	96" x 300" (2438mm x 7620mm)
1025	120" x 300" (3048mm x 7620mm)
	Length available up to 110' (33,000mm) in 60" (1524mm) intervals

Aggregate-Capable Tool Changer

Max Quantity	15 tools
Max Diameter	3.25" (82mm) positions full; 6.5" (165mm) adjacent positions empty
Max Weight	12 lbs each / 96 lbs total (5.4kg / 43.5kg)
Max Length	5" (127mm)

Feed Rate/Traverse

X Axis	2000ipm (50.8mpm)
Y Axis	3150ipm (80mpm)
Z Axis	600ipm (15.2mpm)
Acc/Dec	83 in/sec ²

Axis Travel

525	324" (8230mm) x 84" (2134mm) x 15" (381mm)
625	324" (8230mm) x 84" (2134mm) x 15" (381mm)
825	324" (8230mm) x 164" (4165mm) x 15" (381mm)
1025	324" (8230mm) x 164" (4165mm) x 15" (381mm)

Positioning

Accuracy	±0.0008" (0.02mm) linear axis repeatability
----------	---

Control System

Fanuc Panel i	With integrated PC and 19" touch screen display
---------------	---

Dust Collection

Interface	6" (152mm) dia (1 spindle) recommended volume 900 cfm per spindle
-----------	---

Options

Tooling Package	Tool holders, collets, bench top tool changing block, wrench
Vacuum System	With low vacuum sensing interface
Vacuum Pumps	Started via pushbutton on main operator panel, with remote start relay
Boring Blocks	Available in a variety of configurations, from nine to 25 spindles
Part Labeling	Print labels directly onto parts prior to machining
Safety Equipment	Laser scanners, light curtains, pressure mats
Dual Screen	Additional 19" screen attached to the HMI
Metal Cutting	Mist coolant, dust/chip enclosure, pressure foot for cutting non-ferrous metals
C Axis	Allows use of aggregate tooling, for four axis machining capability
Table	Aluminum universal grid, integrated pop-up roller balls
Spindles	Multiple spindles, programmable head spacing and/or shroud height, head locks